

## Miniature Circuit Breakers PLHT

- High-quality miniature circuit breakers for commercial and residential applications;
- Contact position indicator red and green;
- Accessories suitable for subsequent installation;
- Rated currents up to 125A, B, C and D characteristics;
- Rated breaking capacity up to 25kA according to EN/IEC 60947-2;

Miniature Circuit Breakers PLHT				MW
Rated Current, In	Type Designation	Article Number	Units/Pack	
Characteristic B				
<b>1-pole</b>				
80A	PLHT-B80	247978	12/120	
100A	PLHT-B100	247979	12/120	
125A	PLHT-B125	247980	12/120	
<b>2-pole</b>				
80A	PLHT-B80/2	248004	6/60	
100A	PLHT-B100/2	248005	6/60	
125A	PLHT-B125/2	248006	6/60	
<b>3-pole</b>				
80A	PLHT-B80/3	248030	4/40	
100A	PLHT-B100/3	248031	4/40	
125A	PLHT-B125/3	248032	4/40	
<b>4-pole</b>				
80A	PLHT-B80/4	248042	3/30	
100A	PLHT-B100/4	248043	3/30	
125A	PLHT-B125/4	248044	3/30	
Characteristic C				
<b>1-pole</b>				
80A	PLHT-C80	247987	12/120	
100A	PLHT-C100	247988	12/120	
125A	PLHT-C125	247989	12/120	
<b>2-pole</b>				
80A	PLHT-C80/2	248013	6/60	
100A	PLHT-C100/2	248014	6/60	
125A	PLHT-C125/2	248015	6/60	
<b>3-pole</b>				
80A	PLHT-C80/3	248039	4/40	
100A	PLHT-C100/3	248040	4/40	
125A	PLHT-C125/3	248041	4/40	
<b>4-pole</b>				
80A	PLHT-C80/4	248091	3/30	
100A	PLHT-C100/4	248092	3/30	
125A	PLHT-C125/4	248093	3/30	
Characteristic D				
<b>1-pole</b>				
80A	PLHT-D80	247996	12/120	
100A	PLHT-D100	247997	12/120	
<b>2-pole</b>				
80A	PLHT-D80/2	248022	6/60	
100A	PLHT-D100/2	248023	6/60	
<b>3-pole</b>				
80A	PLHT-D80/3	248048	4/40	
100A	PLHT-D100/3	248049	4/40	
<b>4-pole</b>				
80A	PLHT-D80/4	248100	3/30	
125A	PLHT-D125/4	248101	3/30	

Explanation PLHT

P=xPole, LH=High-quality MCB, T=Ultimate short circuit breaking capacity 10, 15, 25kA

www.teatonelec.com