

MCBs DX³, 6000

thermal magnetic MCBs from 6A to 63A



Conform to IEC60898-1;

Breaking Capacity: 6000-IEC60898-1, 400VAC; 6kA-IEC60947-2, 400VAC;

Do not accept add-on modules;

MCBs DX³, 6000, B Curve

Modules	Nominal Rating, In	Category Number	Quantity/Pack
Single Pole 230/400VAC			
6		4 074 29	12/120
10		4 074 30	12/120
16		4 074 32	12/120
20		4 074 33	12/120
25		4 074 34	12/120
32		4 074 35	12/120
40		4 074 36	12/120
50		4 074 37	12/120
63		4 074 38	12/120
2-Pole 230/400VAC			
6		4 075 06	6/60
10		4 075 07	6/60
16		4 075 09	6/60
20		4 075 10	6/60
25		4 075 11	6/60
32		4 075 12	6/60
40		4 075 13	6/60
50		4 075 14	6/60
63		4 075 15	6/60
3-Pole 230/400VAC			
6		4 075 58	4/40
10		4 075 59	4/40
16		4 075 61	4/40
20		4 075 62	4/40
25		4 075 63	4/40
32		4 075 64	4/40
40		4 075 65	4/40
50		4 075 66	4/40
63		4 075 67	4/40
4-Pole 230/400VAC			
6		4 076 21	3/30
10		4 076 22	3/30
16		4 076 24	3/30
20		4 076 25	3/30
25		4 076 26	3/30
32		4 076 27	3/30
40		4 076 28	3/30
50		4 076 29	3/30
63		4 076 30	3/30

MCBs DX³, 6000, C Curve

Modules	Nominal Rating, In	Category Number	Quantity/Pack
Single Pole 230/400VAC			
6		4 076 66	12/120
10		4 076 68	12/120
16		4 076 70	12/120
20		4 076 71	12/120
25		4 076 72	12/120
32		4 076 73	12/120
40		4 076 74	12/120
50		4 076 75	12/120
63		4 076 76	12/120
2-Pole 230/400VAC			
6		4 077 96	6/60
10		4 077 98	6/60
16		4 078 00	6/60
20		4 078 01	6/60
25		4 078 02	6/60
32		4 078 03	6/60
40		4 078 04	6/60
50		4 078 05	6/60
63		4 078 06	6/60
3-Pole 230/400VAC			
6		4 078 55	4/40
10		4 078 57	4/40
16		4 078 59	4/40
20		4 078 60	4/40
25		4 078 61	4/40
32		4 078 62	4/40
40		4 078 63	4/40
50		4 078 64	4/40
63		4 078 65	4/40
4-Pole 230/400VAC			
6		4 079 24	3/30
10		4 079 26	3/30
16		4 079 28	3/30
20		4 079 29	3/30
25		4 079 30	3/30
32		4 079 31	3/30
40		4 079 32	3/30
50		4 079 33	3/30
63		4 079 34	3/30