

MCBs RX³, 6000

thermal magnetic MCBs from 6A to 63A



Conform to IEC60898-1;

Breaking Capacity: 6000-IEC60898-1, 400VAC; 6kA-IEC60947-2, 400VAC;

Do not accept add-on modules;

MCBs RX³, 6000, B Curve

Modules Nominal Rating, In Category Number Quantity/Pack

Single Pole 230/400VAC

6	4 022 70	12/120
10	4 022 71	12/120
13	-	-
16	4 022 72	12/120
20	4 022 73	12/120
25	4 022 74	12/120
32	4 022 75	12/120
40	4 022 76	12/120
50	4 022 77	12/120
63	4 022 78	12/120

2-Pole 230/400VAC

6	4 022 80	6/60
10	4 022 81	6/60
13	-	-
16	4 022 82	6/60
20	4 022 83	6/60
25	4 022 84	6/60
32	4 022 85	6/60
40	4 022 86	6/60
50	4 022 87	6/60
63	4 022 88	6/60

3-Pole 230/400VAC

6	4 022 90	4/40
10	4 022 91	4/40
13	-	-
16	4 022 92	4/40
20	4 022 93	4/40
25	4 022 94	4/40
32	4 022 95	4/40
40	4 022 96	4/40
50	4 022 97	4/40
63	4 022 98	4/40

4-Pole 230/400VAC

6	4 023 00	3/30
10	4 023 01	3/30
13	-	-
16	4 023 02	3/30
20	4 023 03	3/30
25	4 023 04	3/30
32	4 023 05	3/30
40	4 023 06	3/30
50	4 023 07	3/30
63	4 023 08	3/30

MCBs RX³, 6000, C Curve

Modules Nominal Rating, In Category Number Quantity/Pack

Single Pole 230/400VAC

6	4 023 10	12/120
10	4 023 11	12/120
13	4 023 12	12/120
16	4 023 13	12/120
20	4 023 14	12/120
25	4 023 15	12/120
32	4 023 16	12/120
40	4 023 17	12/120
50	4 023 18	12/120
63	4 023 19	12/120

2-Pole 230/400VAC

6	4 023 21	6/60
10	4 023 22	6/60
13	4 023 23	6/60
16	4 023 24	6/60
20	4 023 25	6/60
25	4 023 26	6/60
32	4 023 27	6/60
40	4 023 28	6/60
50	4 023 29	6/60
63	4 023 30	6/60

3-Pole 230/400VAC

6	4 023 32	4/40
10	4 023 33	4/40
13	4 023 34	4/40
16	4 023 35	4/40
20	4 023 36	4/40
25	4 023 37	4/40
32	4 023 38	4/40
40	4 023 39	4/40
50	4 023 40	4/40
63	4 023 41	4/40

4-Pole 230/400VAC

6	4 023 43	3/30
10	4 023 44	3/30
13	4 023 45	3/30
16	4 023 46	3/30
20	4 023 47	3/30
25	4 023 48	3/30
32	4 023 49	3/30
40	4 023 50	3/30
50	4 023 51	3/30
63	4 023 52	3/30