

MCBs TX³, 6000

thermal magnetic MCBs from 6A to 63A, C curve



Conform to IEC 60898-1;

Compatible with prong-type supply busbars:

Breaking capacity: 6000-IEC 60898-1, 6kA-IEC 60947-2;

Can be equipped with DX3 signalling and remote tripping auxiliaries;

Modules Nominal Rating, In Category Number Quantity/Pack

Single Pole 230/400VAC

6	4 035 74	12/120
10	4 035 75	12/120
16	4 035 76	12/120
20	4 035 77	12/120
25	4 035 78	12/120
32	4 035 79	12/120
40	4 035 80	12/120
50	4 035 81	12/120
63	4 035 82	12/120

2-Pole 230/400VAC

6	4 036 04	6/60
10	4 036 05	6/60
16	4 036 06	6/60
20	4 036 07	6/60
25	4 036 08	6/60
32	4 036 09	6/60
40	4 036 10	6/60
50	4 036 11	6/60
63	4 036 12	6/60

3-Pole 230/400VAC

6	4 036 14	4/40
10	4 036 15	4/40
16	4 036 16	4/40
20	4 036 17	4/40
25	4 036 18	4/40
32	4 036 19	4/40
40	4 036 20	4/40
50	4 036 21	4/40
63	4 036 22	4/40

4-Pole 230/400VAC

6	4 036 24	3/30
10	4 036 25	3/30
16	4 036 26	3/30
20	4 036 27	3/30
25	4 036 28	3/30
32	4 036 29	3/30
40	4 036 30	3/30
50	4 036 31	3/30
63	4 036 32	3/30

RCCBs TX3-Residual Current Circuit Breakers

from 25A to 63A, AC and A types



Conform to IEC61008-1;

Compatible with prong-type supply busbars:

•AC type: detect AC component faults;

•A type: detect AC and DC component faults;

Do not accept add-on modules;

Modules In, A Sensitivity, mA Category Number Quantity/Pack

2-pole 230VAC, AC Type

25	30	4 030 00	1/60
40	30	4 030 01	1/60
63	30	4 030 02	1/60
25	300	4 030 38	1/60
40	300	4 030 39	1/60
63	300	4 030 40	1/60

2-pole 230VAC, A Type

25	30	4 030 35	1/60
40	30	4 030 36	1/60

4-pole 400VAC, AC Type, Neutral on Left-Hand Side

25	30	4 030 04	1/30
40	30	4 030 05	1/30
63	30	4 030 06	1/30

4-pole 400VAC, AC Type, Neutral on Right-Hand Side

25	30	4 030 08	1/30
40	30	4 030 09	1/30
63	30	4 030 10	1/30
25	300	4 030 42	1/30
40	300	4 030 43	1/30
63	300	4 030 44	1/30