

MCBs DX-E 6000 -6kA

thermal magnetic MCBs from 6A to 63A



Conform to IEC60898-1;

Breaking Capacity: 6000-IEC60898-1, 400VAC; 6kA-IEC60947-2, 400VAC;

Do not accept add-on modules;

MCBs DX-E 6000 -6kA, B Curve

Modules Nominal Rating, In Category Number Quantity/Pack

Single Pole 230/400VAC

6	0 032 66	12/120
10	0 032 68	12/120
13	0 032 69	12/120
16	0 032 70	12/120
20	0 032 71	12/120
25	0 032 72	12/120
32	0 032 73	12/120
40	0 032 74	12/120
50	0 032 75	12/120
63	0 032 76	12/120

2-Pole 230/400VAC

6	0 033 08	6/60
10	0 033 10	6/60
13	0 033 11	6/60
16	0 033 12	6/60
20	0 033 13	6/60
25	0 033 14	6/60
32	0 033 15	6/60
40	0 033 16	6/60
50	0 033 17	6/60
63	0 033 18	6/60

3-Pole 230/400VAC

6	0 033 22	4/40
10	0 033 24	4/40
13	0 033 25	4/40
16	0 033 26	4/40
20	0 033 27	4/40
25	0 033 28	4/40
32	0 033 29	4/40
40	0 033 30	4/40
50	0 033 31	4/40
63	0 033 32	4/40

4-Pole 230/400VAC

6	0 033 68	3/30
10	0 033 70	3/30
13	0 033 71	3/30
16	0 033 72	3/30
20	0 033 73	3/30
25	0 033 74	3/30
32	0 033 75	3/30
40	0 033 76	3/30
50	0 033 77	3/30
63	0 033 78	3/30

MCBs DX-E 6000 -6kA, C Curve

Modules Nominal Rating, In Category Number Quantity/Pack

Single Pole 230/400VAC

6	0 033 82	12/120
10	0 033 84	12/120
13	0 033 85	12/120
16	0 033 86	12/120
20	0 033 87	12/120
25	0 033 88	12/120
32	0 033 89	12/120
40	0 033 90	12/120
50	0 033 91	12/120
63	0 033 92	12/120

2-Pole 230/400VAC

6	0 034 29	6/60
10	0 034 31	6/60
13	0 034 32	6/60
16	0 034 33	6/60
20	0 034 34	6/60
25	0 034 35	6/60
32	0 034 36	6/60
40	0 034 37	6/60
50	0 034 38	6/60
63	0 034 39	6/60

3-Pole 230/400VAC

6	0 034 47	4/40
10	0 034 49	4/40
13	0 034 50	4/40
16	0 034 51	4/40
20	0 034 52	4/40
25	0 034 53	4/40
32	0 034 54	4/40
40	0 034 55	4/40
50	0 034 56	4/40
63	0 034 57	4/40

4-Pole 230/400VAC

6	0 034 89	3/30
10	0 034 91	3/30
13	0 034 92	3/30
16	0 034 93	3/30
20	0 034 94	3/30
25	0 034 95	3/30
32	0 034 96	3/30
40	0 034 97	3/30
50	0 034 98	3/30
63	0 034 99	3/30