



Residual Current Circuit Breakers, FH200 Series

Applications: Buildings, both residential and commercial;

Standard: IEC/EN 61008;

Function: Protection against the effects of sinusoidal alternating earth fault currents, protection against indirect contacts and additional protection against direct contacts (with $I_{\Delta n}=30\text{mA}$), command and isolation of resistive and inductive circuits;

Marking: According to IEC 61008;

	Number of Poles	Fault Current	Rated Current, In	Type Code	Order Code	bbn	80 12542	Weight	Units/Pack
	2	30mA	25	FH202 AC-25/0.03	2CSF202006R1250	894209	0.200	1/60	
			40	FH202 AC-40/0.03	2CSF202006R1400	894308	0.200	1/60	
			63	FH202 AC-63/0.03	2CSF202006R1630	894407	0.200	1/60	
	100mA	25	FH202 AC-25/0.1	2CSF202006R2250	894506	0.200	1/60		
		40	FH202 AC-40/0.1	2CSF202006R2400	894605	0.200	1/60		
		63	FH202 AC-63/0.1	2CSF202006R2630	894704	0.200	1/60		
	300mA	25	FH202 AC-25/0.3	2CSF202006R1350	894803	0.200	1/60		
		40	FH202 AC-40/0.3	2CSF202006R3400	894902	0.200	1/60		
		63	FH202 AC-63/0.3	2CSF202006R3630	895008	0.200	1/60		
	4	30mA	25	FH204 AC-25/0.03	2CSF204006R1250	895107	0.350	1/30	
			40	FH204 AC-40/0.03	2CSF204006R1400	895206	0.350	1/30	
			63	FH204 AC-63/0.03	2CSF204006R1630	895305	0.350	1/30	
	100mA	25	FH204 AC-25/0.1	2CSF204006R2250	895404	0.350	1/30		
		40	FH204 AC-40/0.1	2CSF204006R2400	895503	0.350	1/30		
		63	FH204 AC-63/0.1	2CSF204006R2630	895602	0.350	1/30		
	300mA	25	FH204 AC-25/0.3	2CSF204006R1350	895701	0.350	1/30		
		40	FH204 AC-40/0.3	2CSF204006R3400	895800	0.350	1/30		
		63	FH204 AC-63/0.3	2CSF204006R3630	895909	0.350	1/30		
2	30mA	25	FH202 A-25/0.03	2CSF202102R1250	892403	0.200	1/60		
		40	FH202 A-40/0.03	2CSF202102R1400	892502	0.200	1/60		
		63	FH202 A-63/0.03	2CSF202102R1630	892601	0.200	1/60		
4	30mA	25	FH204 A-25/0.03	2CSF204102R1250	892700	0.350	1/30		
		40	FH204 A-40/0.03	2CSF204102R1400	892809	0.350	1/30		
		63	FH204 A-63/0.03	2CSF204102R1630	892908	0.350	1/30		

FH202 AC-40/0.3

FH204 AC-63/0.03